Algorithms and Data Structures: Average-Case Analysis of Quicksort

Quicksort

Divide-and-Conquer algorithm for sorting an array. It works as follows:

1. If the input array has less than two elements, nothing to do ... Otherwise, do the following **partitioning** subroutine: Pick a particular key called the **pivot** and divide the array into two subarrays as follows:

$\leq$ pivot	piv.	$\geq$ pivot

2. Sort the two subarrays recursively.

Quicksort Algorithm

Algorithm $\textsc{Quicksort}(A, p, r)$

```
if p < r then
        q ← Partition(A, p, r)
        Quicksort(A, p, q − 1)
        Quicksort(A, q + 1, r)
```


Partitioning

Algorithm $\textsc{Partition}(A, p, r)$

```
pivot ← A[r]
i ← p − 1
for j ←  p to r − 1 do
        if A[j] ≤ pivot then
                i ← i + 1
                exchange A[i], A[j]
exchange A[i + 1], A[r]
return i + 1
```

Same version as [CLRS]

Analysis of Quicksort

- The **size** of an instance (A, p, r) is $n = r - p + 1$.
- Basic operations for sorting are **comparisons of keys**. We let

$$C(n)$$

be the *worst-case number of key-comparisons* performed by $\textsc{Quicksort}(A, p, r)$. We shall try to determine $C(n)$ as precisely as possible.

- It is easy to verify that the worst-case running time $T(n)$ of $\textsc{Quicksort}(A, p, r)$ is $\Theta(C(n))$ if a single comparison requires time $\Theta(1)$.
(i.e., for $\textsc{Quicksort}$, comparisons *dominate* the running time).
In any case,

$$T(n) = \Theta(C(n) \cdot \text{cost per comparison}).$$

Analysis of $\textsc{Partition}$

- $\textsc{Partition}(A, p, r)$ does *exactly* $n - 1$ comparisons for *every* input of size n.
This is of course apart from any comparisons which may be done inside the recursive calls to $\textsc{Quicksort}$.

Worst-case Analysis of $\textsc{Quicksort}$

- We get the following recurrence for $C(n)$:

$$C(n) = \begin{cases} 0 & \text{if } n \leq 1 \\ \max_{1 \leq k \leq n} \big(C(k-1) + C(n-k)\big) + (n-1) & \text{if } n \geq 2 \end{cases}$$

- Intuitively, worst-case seems to be $k = 1$ or $k = n$, i.e., everything falls on one side of the partition. This happens, e.g., if the array is sorted.

Worst-Case Analysis (cont'd)

- *Lower Bound:* $C(n) \geq \frac{1}{2}n(n+1) = \Omega(n^2)$.
Proof: Consider the situation where we are presented with an array which is already sorted. Then on every iteration, we split into one array of length $(n-1)$, and one of length 0.

$$\begin{aligned} C(n) &\geq C(n-1) + (n-1) \\ &\geq C(n-2) + (n-2) + (n-1) \\ &\vdots \\ &\geq \sum_{i=1}^{n-1} i = \frac{1}{2}n(n-1). \end{aligned}$$

- *Upper Bound:* $C(n) \leq O(n^2)$.
BOARD Bit harder than $\Omega(n^2)$ (must consider all possible inputs).
- Overall, we will show

$$C(n) = \Theta(n^2).$$

Best-Case Analysis

- $B(n)$ = number of comparisons done by QUICKSORT in the best case.
- *Recurrence:*

$$B(n) = \begin{cases} 0 & \text{if } n \leq 1 \\ \min_{1 \leq k \leq n} \big(B(k-1) + B(n-k)\big) + (n-1) & \text{if } n \geq 2 \end{cases}$$

- Intuitively, the best case is if the array is always partitioned into two parts of the same size. This would mean

$$B(n) \approx 2B(n/2) + \Theta(n),$$

which implies $B(n) = \Theta(n \lg(n))$.

Average-Case Analysis

- $A(n)$ = number of comparisons done by QUICKSORT on average if all input arrays of size n are considered equally likely.
- **Intuition:** The average case is closer to the best case than to the worst case, because only **repeatedly very unbalanced** partitions lead to the worst case.
- *Recurrence:*

$$A(n) = \begin{cases} 0 & \text{if } n \leq 1 \\ \sum_{k=1}^{n} \frac{1}{n}\big(A(k-1) + A(n-k)\big) + (n-1) & \text{if } n \geq 2 \end{cases}$$

- *Solution:*

$$A(n) \approx 2n \ln(n).$$

Average Case Analysis in Detail

We shall prove that for all $n \geq 1$ ("sufficiently large") we have

$$A(n) \leq 2 \ln(n)(n+1). \qquad (\star)$$

Average Case Analysis in Detail

We shall prove that for all $n \geq 1$ ("sufficiently large") we have

$$A(n) \leq 2 \ln(n)(n+1). \qquad (\star)$$

(Note $(\star)$ holds trivially for $n = 1$, because $\ln(1) = 0$)

Average Case Analysis in Detail

We shall prove that for all $n \geq 1$ ("sufficiently large") we have

$$A(n) \leq 2\ln(n)(n+1). \qquad (\star)$$

(Note $(\star)$ holds trivially for $n = 1$, because $\ln(1) = 0$)
So assume that $n \geq 2$. We have

$$A(n) = \sum_{1 \leq k \leq n} \frac{1}{n}\big(A(k-1) + A(n-k)\big) + (n-1)$$

Average Case Analysis in Detail

We shall prove that for all $n \geq 1$ ("sufficiently large") we have

$$A(n) \leq 2\ln(n)(n+1). \qquad (\star)$$

(Note $(\star)$ holds trivially for $n = 1$, because $\ln(1) = 0$)
So assume that $n \geq 2$. We have

$$A(n) = \sum_{1 \leq k \leq n} \frac{1}{n}\big(A(k-1) + A(n-k)\big) + (n-1)$$

$$= \frac{2}{n}\sum_{k=0}^{n-1} A(k) + (n-1).$$

Average Case Analysis in Detail

We shall prove that for all $n \geq 1$ ("sufficiently large") we have

$$A(n) \leq 2\ln(n)(n+1). \qquad (\star)$$

(Note $(\star)$ holds trivially for $n = 1$, because $\ln(1) = 0$)
So assume that $n \geq 2$. We have

$$A(n) = \sum_{1 \leq k \leq n} \frac{1}{n}\big(A(k-1) + A(n-k)\big) + (n-1)$$

$$= \frac{2}{n}\sum_{k=0}^{n-1} A(k) + (n-1).$$

Thus

$$nA(n) = 2\sum_{k=0}^{n-1} A(k) + n(n-1). \qquad (\star\star)$$

Average Case Analysis in Detail

We shall prove that for all $n \geq 1$ ("sufficiently large") we have

$$A(n) \leq 2\ln(n)(n+1). \qquad (\star)$$

(Note $(\star)$ holds trivially for $n = 1$, because $\ln(1) = 0$)
So assume that $n \geq 2$. We have

$$A(n) = \sum_{1 \leq k \leq n} \frac{1}{n}\big(A(k-1) + A(n-k)\big) + (n-1)$$

$$= \frac{2}{n}\sum_{k=0}^{n-1} A(k) + (n-1).$$

Thus

$$nA(n) = 2\sum_{k=0}^{n-1} A(k) + n(n-1). \qquad (\star\star)$$

Average Case Analysis in Detail (cont'd)

Applying $(\star\star)$ to $(n-1)$ for $n \geq 3$, we obtain

$$(n-1)A(n-1) = 2\sum_{k=0}^{n-2} A(k) + (n-1)(n-2).$$

Average Case Analysis in Detail (cont'd)

Applying $(\star\star)$ to $(n-1)$ for $n \geq 3$, we obtain

$$(n-1)A(n-1) = 2\sum_{k=0}^{n-2} A(k) + (n-1)(n-2).$$

Subtracting this equation from $(\star\star)$ (when $n \geq 3$)

$$nA(n) - (n-1)A(n-1) = 2A(n-1) + n(n-1) - (n-1)(n-2),$$

Average Case Analysis in Detail (cont'd)

Applying $(\star\star)$ to $(n-1)$ for $n \geq 3$, we obtain

$$(n-1)A(n-1) = 2\sum_{k=0}^{n-2} A(k) + (n-1)(n-2).$$

Subtracting this equation from $(\star\star)$ (when $n \geq 3$)

$$nA(n) - (n-1)A(n-1) = 2A(n-1) + n(n-1) - (n-1)(n-2),$$

thus

$$nA(n) = (n+1)A(n-1) + 2n - 2,$$

Average Case Analysis in Detail (cont'd)

Applying $(\star\star)$ to $(n-1)$ for $n \geq 3$, we obtain

$$(n-1)A(n-1) = 2\sum_{k=0}^{n-2} A(k) + (n-1)(n-2).$$

Subtracting this equation from $(\star\star)$ (when $n \geq 3$)

$$nA(n) - (n-1)A(n-1) = 2A(n-1) + n(n-1) - (n-1)(n-2),$$

thus

$$nA(n) = (n+1)A(n-1) + 2n - 2,$$

and therefore

$$\frac{A(n)}{n+1} = \frac{A(n-1)}{n} + \frac{2n-2}{n(n+1)} \leq \frac{A(n-1)}{n} + \frac{2}{n}$$

Average Case Analysis in Detail (cont'd)

Applying ($\star\star$) to $(n-1)$ for $n \geq 3$, we obtain

$$(n-1)A(n-1) = 2\sum_{k=0}^{n-2} A(k) + (n-1)(n-2).$$

Subtracting this equation from ($\star\star$) (when $n \geq 3$)

$$nA(n) - (n-1)A(n-1) = 2A(n-1) + n(n-1) - (n-1)(n-2),$$

thus

$$nA(n) = (n+1)A(n-1) + 2n - 2,$$

and therefore

$$\frac{A(n)}{n+1} = \frac{A(n-1)}{n} + \frac{2n-2}{n(n+1)} \leq \frac{A(n-1)}{n} + \frac{2}{n}$$

We now apply unfold-and-sum to this recurrence (stopping at $n = 2$):

$$\begin{aligned} \frac{A(n)}{n+1} &\leq \frac{A(n-1)}{n} + \frac{2}{n} \\ &\vdots \end{aligned}$$

Average Case Analysis in Detail (cont'd)

$$\frac{A(n)}{n+1} \leq \frac{A(n-2)}{n-1} + \frac{2}{n} + \frac{2}{n-1}$$

Average Case Analysis in Detail (cont'd)

$$\begin{aligned} \frac{A(n)}{n+1} &\leq \frac{A(n-2)}{n-1} + \frac{2}{n} + \frac{2}{n-1} \\ &\vdots \\ &\leq \frac{A(2)}{3} + 2\sum_{k=3}^{n} \frac{1}{k} \end{aligned}$$

Average Case Analysis in Detail (cont'd)

$$\begin{aligned} \frac{A(n)}{n+1} &\leq \frac{A(n-2)}{n-1} + \frac{2}{n} + \frac{2}{n-1} \\ &\vdots \\ &\leq \frac{A(2)}{3} + 2\sum_{k=3}^{n} \frac{1}{k} \\ &= \frac{3}{3} + 2\sum_{k=3}^{n} \frac{1}{k} \quad = \quad 2\sum_{k=2}^{n} \frac{1}{k}. \end{aligned}$$

Average Case Analysis in Detail (cont'd)

$$\begin{aligned}
\frac{A(n)}{n+1} &\leq \frac{A(n-2)}{n-1} + \frac{2}{n} + \frac{2}{n-1} \\
&\vdots \\
&\leq \frac{A(2)}{3} + 2\sum_{k=3}^{n} \frac{1}{k} \\
&= \frac{3}{3} + 2\sum_{k=3}^{n} \frac{1}{k} \quad = \quad 2\sum_{k=2}^{n} \frac{1}{k}.
\end{aligned}$$

It is easy to verify this result by induction. Thus

$$\frac{A(n)}{n+1} \leq 2\sum_{k=2}^{n} \frac{1}{k} = 2\sum_{k=1}^{n-1} \frac{1}{k+1} \leq 2\int_1^n \frac{1}{x} = 2\ln(n).$$

Multiplying by $(n+1)$ completes the proof of $(\star)$.

Improvements

- Use insertion sort for small arrays.
- Iterative implementation.

Main Question

Is there a way to avoid the bad worst-case performance, and in particular the bad performance on sorted (or almost sorted) arrays?

Different strategies for choosing the pivot-element help (in practice).

Median-of-Three Partitioning

Idea: Use the median of the first, middle, and last key as the pivot.

Algorithm $\text{M3Partition}(A, p, r)$

1. exchange $A[(p+r)/2]$, $A[r-1]$
2. **if** $A[p] > A[r-1]$ **then** exchange $A[p]$, $A[r-1]$
3. **if** $A[p] > A[r]$ **then** exchange $A[p]$, $A[r]$
4. **if** $A[r-1] > A[r]$ **then** exchange $A[r-1]$, $A[r]$
5. $\text{Partition}(A, p+1, r-1)$

Note that $\text{M3Partition}(A, p, r)$ only requires 1 more comparison than $\text{Partition}(A, p, r)$

Median-of-Three Partitioning (cont'd)

Algorithm $\text{M3Quicksort}(A, p, r)$

1. **if** $p < r$ **then**
2. $\quad q \leftarrow \text{M3Partition}(A, p, r)$
3. $\quad \text{M3Quicksort}(A, p, q-1)$
4. $\quad \text{M3Quicksort}(A, q+1, r)$

In can be shown that the worst-case running time of M3Quicksort is still $\Theta(n^2)$, but at least in the case of an almost sorted array (and in most other cases that are relevant in practice) it is very efficient.

Randomized Quicksort

Idea: Use key of random element as the pivot.

Algorithm RPartition(A, p, r)

1. $k \leftarrow$ Random(p, r) $\quad\triangleright$ choose k randomly from $\{p, \ldots, r\}$
2. exchange $A[k]$, $A[r]$
3. Partition(A, p, r)

Algorithm Randomized Quicksort(A, p, r)

1. **if** $p < r$ **then**
2. $\quad q \leftarrow$ RPartition(A, p, r)
3. $\quad$ Randomized Quicksort$(A, p, q-1)$
4. $\quad$ Randomized Quicksort$(A, q+1, r)$

Analysis of Randomized Quicksort

The running time of Randomized Quicksort on an input of size n is a **random variable**.

An analysis similar to the average case analysis of Quicksort shows:

Theorem

For all inputs (A, p, r), the **expected number of comparisons** *performed during a run of* Randomized Quicksort *on input (A, p, r), is at most $2\ln(n)(n+1)$, where $n = r - p + 1$.*

Corollary

Thus the **expected running time** *of* Randomized Quicksort *on any input of size n is $\Theta(n \lg(n))$.*

Reading Assignment

Sections 7.2, 7.3, 7.4 of [CLRS] (edition 2 or 3)

Problems

1. Convince yourself that Partition works correctly by working a few examples, or (better) try to prove that it works correctly.
2. In our proof of the Average-running time $A(n)$, we can think of the input as being some permutation of $(1, \ldots, n)$, and assume all permutations are equally likely. Why does this explain the $1/n$ factor in the recurrence on slide 10?
3. Show that if the array is initially in decreasing order, then the running time is $\Theta(n^2)$.
   (the $O(n^2)$ is already taken care of on slide 8 (well, the board note), the $\Omega(n^2)$ involves considering Partition on a decreasing array).