

Decision Making *in Robots and Autonomous Agents*

Safety in Engineered Systems: Introducing the Issues

Subramanian Ramamoorthy
School of Informatics

15 March 2019

Plan for lectures on safety and privacy

1. Two parts

- This lecture on introducing core concerns (case study, approach to assurance, typical privacy issues)
- Next lecture on technical tools aimed at addressing these (Bayesian formulation, formal methods, differential privacy)


2. Introducing safety

- How did the industry thinking evolve
- Case studies of accidents and what they tell us
- Safety and assurance cases
- Emerging issues: through example of autonomous vehicles

Why? Example 1





[Source: aslib.co.uk]



[Source: www.iff.fraunhofer.de]

Traditional Notions of Robot Safety



Deployed robot safety systems


Robots, depending on the task, may generate paint mist, welding fumes, plastic fumes, etc. In general, the robot, on occasion is used in environments or tasks too dangerous for workers, and as such creates hazards not specific to the robot but specific to the task.

Examples of Accidents

Example 1: First fatal robot-related accident in the U.S.

On July 21, 1984, a die cast operator was working with an automated die cast system utilizing a Unimate Robot, which was programmed to extract the casting from the die-cast machine, dip it into a quench tank and insert it into an automatic trim press.

A neighboring employee discovered the victim pinned between the right rear of the robot and a safety pole in a slumped but upright position. The victim died five days later in the hospital.




Examples of Accidents

Example 2:

A material handling robot was operating in its automatic mode and a worker violated safety devices to enter the robot work cell. The worker became trapped between the robot and a post anchored to the floor, was injured and died a few days later.


Example 3:

A maintenance person climbed over a safety fence without turning off power to a robot and performed tasks in the robot work zone while it was temporarily stopped. When the robot recommenced operation, it pushed the person into a grinding machine, killing the person.




How is 'Safety' Implemented?

Example 1: Monitor and increase safety of tool zones




How is 'Safety' Implemented?

Example 2: Safe stand still/
direct loading of a robot



Example 3: Safe axis ranges
with track motions



[Source: G. Cui et al., Ontario]

Characterizing an *Unsafe* Robot

Human Interaction

Control Errors


Unauthorized Access

Mechanical Failures

Environmental Sources

Power Systems

Improper Installation



Why? Example 2

HOME SEARCH

The New York Times

TECHNOLOGY

855 CO

Google's Driverless Cars Run Into Problem: Cars With Drivers

By MATT RICHTEL and CONOR DOUGHERTY SEPT. 1, 2015



How will you characterise 'unsafe' in this context? Discuss!

Are these Issues Unique to Robotics?

NO!

- Many other engineering systems have been through a similar path towards understanding safety
- Avionics, maritime systems, nuclear reactors, ...
- ... office printers!
- Many famous examples of failures which are systemic rather than individual component driven

Perrow's Notion of *Normal Accidents*

- While many initial accident analyses have blamed the human operators, the real fault lies in system design
- Certain high-risk systems, because of the way they configure sequences of subsystems, are *naturally* prone to eventually resulting in an accident.
- So, Three Mile Island was a Normal Accident

(cars and humanoids too?!)




Normal Accidents: Core Argument


- Interactive Complexity
 - Failures of two components interact in an unexpected way
- Tightly Coupled
 - Processes that are parts of a system that happen quickly and cannot be turned off or isolated
- Perrow's Thesis: Tightly coupled systems with high interactive complexity will have Normal Accidents

Example: Three Mile Island


- Perhaps the most famous nuclear accident in the US
- On March 16, 1979, the movie China Syndrome (addresses social issues around nuclear accidents) is released
- 12 days later, March 28, 1979, the worst civilian nuclear accident in the US occurred at the Three Mile Island Nuclear Power Plant on the Susquehanna River, south of Harrisburg, PA.



Three Mile Island: Location



Example: Three Mile Island



Cooling System Setup

- Primary Cooling System
 - High pressure, radioactive, water circulating through the reactor.
 - Heat Exchanger transfers heat to the secondary system
- Secondary Cooling System
 - Cools the primary cooling system
 - Creates steam to run the turbines to generate electricity
 - Due to thin tubes in the turbine it must be very pure
Continuously cleaned by a "polisher system"

A Sequence of Events

- The polisher leaked about a cup a day of water through a seal
- Water vapor got into a pneumatic system that drives some instruments
- This water vapor interrupted pressure to two valves in the feedwater system, which caused two feedwater pumps to shut down
- Lack of flow in the secondary system triggered a safety system that shut down the turbines
- This was the first indication of trouble to the operators
- At this point the reactor still needs to be cooled – or else

Sequence of Events: Emergency System

- An emergency feedwater system starts up to pump stored cold water through the secondary system to remove the accumulating heat
- The pumps were running, but valves on the pipes were incorrectly left closed from prior maintenance
- The operators insist they were left open; checklist says so
- A Repair Tag on a broken indicator hung over the indicator on the control panel that indicated that the valves were closed
- Redundant pipes, redundant pumps, and redundant valves, all thwarted by having the two valves physically at the same place and mis-set
- Eight minutes later they noticed they were shut by then the damage was done

No Cooling = Reactor Heats Up

- Due to overheating the reactor "scrammed" automatically
- This shuts down the reaction
- Enough heat remains in the reactor to require a normal working cooling several days to cool off
- Without cooling the pressure goes up
- An ASU Automatic Safety Device takes over to temporarily relieve the pressure: the Pilot Operated Relief Valve (PORV)

PORV (Pilot Operated Relief Valve)

- The PORV is supposed to vent pressure briefly, and then reclose
- If it stays open too long liquid escapes, pressure in the reactor drops, steam forms causing voids in the water, cooling is impaired and some places get yet hotter
- Thirty-two thousand gallons of water eventually went out this unclosed valve
- There was an indication on the control panel that the message to reseal had been sent to the valve
- However, no indication was available that it had reseated
- We are now thirteen seconds into the "transient"
- An indicator shows that there is extra water from an unknown source

Automatic Cooling Pump Starts

- This is another automatic safety system that pumps water to cool the reactor automatically starts at 13 seconds. The second was manually started by the operator
- For three minutes it looked like the core was being cooled successfully
- However, apparently due to the steam voids, the cooling was not happening
- The secondary steam generators were not getting water and boiled dry - at the same time water was flowing out of the primary cooling system through the stuck pressure relief valve

High Pressure Injection Starts

- This is an automatic emergency device that forces cold water into the reactor to cool it down.
- The reactor was flooded for two minutes, and then the operators drastically cut back the flow. This was regarded as the key operator error; what they did not realize was that the water was flowing out the PORV and the core would become uncovered
- Two dials confused the operators:
 - one said the pressure in the reactor was rising
 - the other said it was falling
- The Kemeny commission thought the operators should have realized this meant LOCA (Loss of Coolant Accident)

What is it Like in Control Room?

- Three audible alarms are making a din
- Many of the 1,600 indicator lights are blinking
- The computer is way behind in printing out error messages
- It turns out they can only be printed, not spooled to disk, to see the current condition they would have to purge the printer and lose potentially valuable information
- The reactor coolant pumps begin the bang and shake, due to cavitation from lack of water to pump-they are shut off

Stuck Open PORV Valve Discovered

- The operators checked the valve and found it open
- They closed it
- With some trepidation since they were messing with a safety system
- The reactor core had been uncovered at this point and had partially melted
- Another 30 minutes without coolant and it would probably have been a total melt down (e.g., Chernobyl)

Tell tale Signs

- The whole system is never all up and working as designed thus it is hard to understand
- When things start to fail the system is even harder to understand
- Safety systems are not always working
 - some are down, and known to be
 - some are accidentally turned off
 - some are not set properly
 - others fail to work when needed
- There are often not direct indicators of what is happening operators figure it out indirectly

Can this happen elsewhere? With/to robots?

Safety Case: How to Approach Assurance?

- As we saw, early attempts set in place prescriptive rules and safety codes to which adherence was mandatory
 - This includes standards, e.g., by ISO or SAE
- However, many engineered systems are so complex that this could rule out the entire intended operation if done in a heavy handed way
- Alternative: ask developers and operators to construct well reasoned arguments that their systems achieve acceptable levels of safety
- These arguments, together with supporting evidence, are typically referred to as a “safety case”

Safety Cases

- The purpose of a safety case:
A safety case should communicate a clear, comprehensive and defensible argument that a system is acceptably safe to operate in a particular context
- Safety cases are already adopted in many industries, including defence, aerospace, railways and automotive sectors.
- Based on such practice, we can extract a few key attributes of what makes a good and useful safety case

Aspects of a Safety Case

- **‘argument’**: the case exists to communicate an argument, to demonstrate how someone can reasonably conclude that a system is acceptably safe from the available evidence
- **‘clear’**: it is a device for communicating ideas and information to a third party, e.g., regulator
- **‘system’**: this could be anything from a network of pipes to a software module with parameters or operating procedures
- **‘acceptably’**: In most applications, “absolute” safety is impossible. So, the case is argument to say how the system is **safe enough** (as per some notion of tolerable risk)
- **‘context’**: most systems are only safe within a context of use, which should be defined in the safety case


Safety Case as a Physical Artifact

- Comprehensive and structured set of documentation
- To ensure safety can be demonstrated with reference to:
 - Arrangements and organisation, including emergency arrangements
 - Safety analyses
 - Compliance with standards and best practice
 - Acceptance tests
 - Audits and inspections
 - Feedback

Definition according to UK MoD

How to Argue?

[T. Kelly, SAE 04AE-149, 2003]



Communicating Safety Arguments: Typical Example in Textual Form

The Defence in Depth principle (P65) has been addressed in this system through the provision of the following:

- Multiple physical barriers between hazard source and the environment (see Section X)
- A protection system to prevent breach of these barriers and to mitigate the effects of a barrier being breached (see Section Y)


[T. Kelly, SAE 04AE-149, 2003]

... however, writing down long arguments can be both cumbersome and error-prone when teams of engineers work on such arguments


Formal notation: Goal-structuring Notation

GSN: a graphical argumentation notation - explicitly represents the individual elements of any safety argument

Vocabulary:




Example Goal Structure for a Braking System



[T. Kelly, SAE 04AE-149, 2003]


Sketch of a Preliminary Safety Argument




[T. Kelly, SAE 04AE-149, 2003]

Different Views of Development and Safety Lifecycles


Design cycle:



Desired integrated Safety cycle:



Historical Safety cycle:



Current Issues: Driver Assist & Autonomous Vehicles




Why Difficult? Typical Operating Scenarios



Issues:


- Dynamic & Open Environments
- Incompleteness & Uncertainty (Model & Perception)
- Human in the loop (Social & Interaction Constraints)

Bayesian Perception Approach



Bayesian Perception for ADAS/AV

- Estimate Spatial occupancy
- Analyze Motion Field (using Bayesian filtering)
- Initially, reason at the Grid level (no object segmentation, just prob. of occupancy, o , given observation z and state c)
- Then, register other objects on top of this data structure



Can We Ensure Safety, Always?

- Active topic of discussion
- Consider some examples due to A. Shashua*

Q: Can the central car avoid all collisions?



* [S. Shalev-Shwartz, S. Shammah, A. Shashua, On a formal model of safe and scalable self-driving cars. arXiv preprint arXiv:1708.06374, 2017]


Shashua's Approach to Safety

In practice, the AV needs to know two things:

- **Safe State:** This is a state where there is no risk that the AV will cause an accident, even if other vehicles take unpredictable or reckless actions.
- **Default Emergency Policy:** This is a concept that defines the most aggressive evasive action that an AV can take to maintain or return to a Safe State.

They coin the term **Cautious Command** to represent the complete set of commands that maintains a Safe State. Set a hard rule that the AV will never make a command outside of the set of Cautious Commands. This ensures that the planning module itself will never cause an accident.

Example: Safe Longitudinal Distance





Safe Distance Formula

$$d_{\min} = L + T_f [v_r - v_f + \rho (a_a + a_b)] - \frac{\rho^2 a_b}{2} + \frac{(T_r - T_f)(v_r + \rho a_a - (T_f - \rho) a_b)}{2}$$

- L is the average length of the vehicles
- ρ is the response time of the rear vehicle
- v_r, v_f are the velocities of the rear/front vehicles
- a_a, a_b are the maximal acceleration/braking of the vehicles
- T_f is the time for the front car to reach a full stop if it would apply maximal braking
- T_r is the time for the rear car to reach a full stop if it would apply maximal acceleration during the response time, and from there on maximal braking

Prospects for the Future

- Can more generic policy learning, e.g., reinforcement learning to navigate past crowded intersection, respect these?
 - Formal methods often use concept of “guard condition”
 - How best to define in open-ended environment?
- Can we avoid “frozen robots”?



[Trautman + Krause, IROS 2010]