Models of Human Parsing Informatics 2A: Lecture 26

John Longley

20 November 2015



Human Parsing

- Cognitive Constraints
- Garden Paths
- Dimensions of Parsing
- 2 Experimental Data
 - Eye-tracking
 - Reading
- Bottom-Up Parser
 - Parallel Parsing
 - Properties

4 Left Corner Parser

- I eft Corner Chart
- Serial Parsing
- Properties

Reading: J&M, ch. 9 (pp. 350–352), ch. 12 (pp. 467–473), ch. 13 (pp. 491–496).

Cognitive Constraints Garden Paths Dimensions of Parsing

Human Parsing

So far, we looked at parsing from an engineering perspective. However, humans also do parsing to understand language.

The mathematical and algorithmic tools in this course can be used to analyze human parsing (human sentence processing). This is the domain of psycholinguistics.

Cognitive Constraints Garden Paths Dimensions of Parsing

Human Parsing

So far, we looked at parsing from an engineering perspective. However, humans also do parsing to understand language.

The mathematical and algorithmic tools in this course can be used to analyze human parsing (human sentence processing). This is the domain of psycholinguistics.

To study human parsing, we need:

• experimental data that tell us how humans parse;

Cognitive Constraints Garden Paths Dimensions of Parsing

Human Parsing

So far, we looked at parsing from an engineering perspective. However, humans also do parsing to understand language.

The mathematical and algorithmic tools in this course can be used to analyze human parsing (human sentence processing). This is the domain of psycholinguistics.

To study human parsing, we need:

- experimental data that tell us how humans parse;
- cognitive constraints derived from these data (e.g., incrementality, garden paths, memory limitations);

Cognitive Constraints Garden Paths Dimensions of Parsing

Human Parsing

So far, we looked at parsing from an engineering perspective. However, humans also do parsing to understand language.

The mathematical and algorithmic tools in this course can be used to analyze human parsing (human sentence processing). This is the domain of psycholinguistics.

To study human parsing, we need:

- experimental data that tell us how humans parse;
- cognitive constraints derived from these data (e.g., incrementality, garden paths, memory limitations);
- parsing models (and algorithms that implement them) that respect these constraints;

Cognitive Constraints Garden Paths Dimensions of Parsing

Human Parsing

So far, we looked at parsing from an engineering perspective. However, humans also do parsing to understand language.

The mathematical and algorithmic tools in this course can be used to analyze human parsing (human sentence processing). This is the domain of psycholinguistics.

To study human parsing, we need:

- experimental data that tell us how humans parse;
- cognitive constraints derived from these data (e.g., incrementality, garden paths, memory limitations);
- parsing models (and algorithms that implement them) that respect these constraints;
- an evaluation of the models against the data.

Cognitive Constraints Garden Paths Dimensions of Parsing

Incrementality

Parsing: extracting syntactic structure from a string; prerequisite for assigning a meaning to the string.

The human parser builds structures incrementally (word by word) as the input comes in.


This can lead to local ambiguity.

Example:

- (1) The athlete realized his potential ...
 - a. ... at the competition.
 - b. ... would make him a world-class sprinter.


Cognitive Constraints Garden Paths Dimensions of Parsing

Incrementality



Cognitive Constraints Garden Paths Dimensions of Parsing

Incrementality



Cognitive Constraints Garden Paths Dimensions of Parsing

Garden Paths

- Early commitment: when it reaches *potential*, the processor has to decide which structure to build.
- If the parser makes the wrong choice (e.g., NP reading for sentence (1-b)) it needs to backtrack and revise the structure.
- A garden path occurs, which typically results in longer reading times (and reverse eye-movements).
- Some garden paths are so strong that the parser fails to recover from them.

Cognitive Constraints Garden Paths Dimensions of Parsing

Garden Paths

More examples of garden paths:

- (2) a. The horse raced past the barn fell.
 - b. I convinced her children are noisy.
 - c. Until the police arrest the drug dealers control the street.
 - d. The old man the boat.
 - e. We painted the wall with cracks.
 - f. Fat people eat accumulates.
 - g. The cotton clothing is usually made of grows in Mississippi.
 - h. The prime number few.

Cognitive Constraints Garden Paths Dimensions of Parsing

Dimensions of Parsing

In addition to incrementality, a number of properties are important when designing a model of the human parser:

- Directionality: the parser can process sentence bottom-up (from the words up) or top-down (from the non-terminals down). Evidence that the human parser combines both strategies.
- Parallelism: a serial parser maintains only one structure at a time; a parallel parser pursues all possible structures. Controversial issue; evidence for both serialism and limited parallelism.
- Interactivity: the parser can be encapsulated (only access to syntactic information) or interactive (access to semantic information, context). Evidence for limited interactivity.

Eye-tracking Reading

Eye-tracking

An eye-tracker makes it possible to record the eye-movements of subjects while they are performing a cognitive task:

- looking at a scene;
- driving a vehicle;
- using a computer;
- reading a text.

Mind's Eye Hypothesis: where subjects are looking indicates what they are processing. How long they are looking at it indicates how much processing effort is needed.

Eye-tracking Reading

Eye-tracking



A head-mounted, video-based eye-tracker.



Eye-tracking Reading

Eye-movements and Reading

Let's look at eye-tracking data for reading in detail:

- eye-movements are recorded while subjects read texts;
- \bullet very high spatial (0.15° visual angle) and temporal (1 ms) accuracy;
- eye movements in reading are saccadic: a series of relatively stationary periods (fixations) between very fast movements (saccades);
- average fixation time is about 250 ms; can be longer or shorter, depending on ease or difficulty of processing;
- typically test a number of subjects, with a number of test sentences, and statistical analysis done on results.

Eye-tracking Reading

Eye-movements and Reading

Buck did not read the newspapers, or he would have known that trouble was brewing, not alone for himself, but for every tide-water dog, strong of muscle and with warm, long hair, from Puget Sound to San Diego. Because men, groping in the Arctic darkness, had found a yellow metal, and because steamship and transportation companies were booming the find, thousands of men were rushing into the Northland. These men wanted dogs, and the dogs they wanted were heavy dogs, with strong muscles by which to toil, and furry coats to protect them from the frost.

Buck lived at a big house in the sun-kissed Santa Clara Valley. Judge Miller's place, it was called. It stood back from the road, half hidden among the trees, through which glimpses could be caught of the wide cool veranda that ran around its four sides.

Eye-tracking Reading

Eye-movements and Reading

Buck did not read the newspapers, or he would have known that thouse was brewing, not alone for himself, but for every tide-water dog, strong of muscle and with warm, long bair, from Puget Sound to San Diego. Because men groping in the Arctic darkness, had found a yellow metal, and because steamship and transportation companies were booming the find, thousands of men were rushing into the Northland. These men wanted dogs, and the dogs they wanted were freavy dogs, with strong muscles by which to toil, and fourly coats to protect them from the frest.

¹²⁰ ¹²⁴ ¹²⁶ ¹²⁶ ¹²⁷ ¹²⁶ ¹²⁶

Eye-tracking Reading

Eye-movements and Reading

Busk did not read the newspapers, or he wayte have mown that the set of the s

Buck fried at a Gig house in the sun kissed Santa Clara Valley. Rudde Millers place, it was called it stood back from the road, half hidden arrong the trees, through which glimps could be caught of the wide opol veranda that ran around its four side

Eye-tracking Reading

Eye-movements and Reading

We can use the data generated by eye-tracking experiments to investigate how the human parser works. For example:

- evidence for garden paths comes from increased reading times, and more reverse saccades, when reading certain words;
- evidence for incrementality comes from studies where participants view visual scenes while listening to sentences;
- evidence for interactivity comes from the fact that semantic properties of words influence reading times in the same way as syntactic ones.

We will look at how to model these properties by building a parser that mimics human parsing behavior.

Eye-tracking Reading

Clicker Question

Which of the following sentences in not a garden path?

- The man returned to his house was happy.
- The complex houses married and single soldiers and their families.
- O The tomcat that curled up on the cushion seemed friendly.
- The sour drink from the ocean.

Parallel Parsing Properties

A Small Grammar of English

We need a grammar of English to study our parsing models.

Phrasal categories:

S: sentence, NP: noun phrase, VP: verb phrase

Syntactic categories (aka parts of speech): Det: determiner, CN: common noun, TV: transitive verb


Phrase structure rules:

S	\rightarrow	NP VP	Det	\rightarrow	the
NP	\rightarrow	Det CN	CN	\rightarrow	kittens
VP	\rightarrow	TV NP	ΤV	\rightarrow	bite
			CN	\rightarrow	dog

Parallel Parsing Properties

Syntax Tree

The syntax tree for the sentence the kittens bite the dog:




Let's assume that this tree is constructed a CYK parser as discussed in lecture 16.

Parallel Parsing Properties

A Bottom-Up Parallel Parser

Example of a CYK chart (in graph notation):



Parallel Parsing Properties

Properties of the Model

This offers a simple model of the human parser with the following properties:

- bottom-up: parsing is driven by the addition of words to the chart; chart is expanded upwards from lexical to phrasal categories;
- limited incrementality: when a new word appears, all possible edges are added to the chart; then the system waits for the next word;
- parallelism: all chart edges are added at the same time; multiple analyses are pursued.

Parallel Parsing Properties

Properties of the Model

This offers a simple model of the human parser with the following properties:

- bottom-up: parsing is driven by the addition of words to the chart; chart is expanded upwards from lexical to phrasal categories;
- limited incrementality: when a new word appears, all possible edges are added to the chart; then the system waits for the next word;
- parallelism: all chart edges are added at the same time; multiple analyses are pursued.

Doesn't fit with observed data. Processing time isn't correlated to number of edges to be added. And on the above model, garden paths wouldn't be a particular problem.

Left Corner Chart Serial Parsing Properties

Left Corner Parsing

Cognitively plausible incrementality: each word is integrated into the structure as it appears (no unconnected words).


This can be achieved using left corner chart parsing. This is similar to Earley parsing, but with a more 'bottom-up' Predictor:

PREDICTOR $(A \to \alpha \bullet, [i, k])$ for each $(B \to A\beta)$ in Grammar_Rules_For(B, grammar): enqueue $((B \to A \bullet \beta, [i, k]), chart[i])$

Completer and Scanner are basically the same as in Earley (Scanner gets to start).

Left Corner Chart Serial Parsing Properties

Example of a Left Corner Chart



Left Corner Charl Serial Parsing Properties

Serial Parsing

If parsing was fully parallel, all analyses of a sentence would be equally available; there would be no garden paths.

In the literature, two types of models have been assumed:

- ranked parallel: multiple structures are pursued in parallel; they are ranked in order of preference; garden paths occur if a low-ranked structure turns out to be correct;
- serial: only one structure is pursued; if it turns out to be incorrect, then a garden path occurs.

Let's assume a serial left-corner parser with backtracking.

Left Corner Charl Serial Parsing Properties

Serial Parsing

Serial left-corner parser with backtracking:

- At each point of ambiguity, the parser has to choose one structure, instead of adding all possible structures to the chart;
- if this structure turns out to be incorrect; the parser has to backtrack;
- at the last point of ambiguity, the incorrect structure is removed from the chart, and an alternative one is added to the chart instead;
- this requires additional data structures to keep track of the choice points and the choices made.

Left Corner Chart Serial Parsing Properties

Properties of the Model

Properties of the left corner model:

- this model will parse garden path sentences such as *the horse* raced past the barn fell;
- extensive backtracking will occur for such sentences; only possible if the stack size of the choice point stack is sufficient;

Potential issues:

- backtracking requires that parse failure is detected; requires that the parser knows where the sentence boundaries are;
- processing order is fixed; context or experience is not taken into account; no attempt to minimize backtracking.

Left Corner Charl Serial Parsing Properties

Summary

- The human parser builds syntactic structure in response to strings of words;
- parsing models have to capture the incrementality of human parsing and account for ambiguity resolution (garden paths);
- parsing models can be implemented using a chart (representing partial syntactic structure);
- a simple bottom-up parser assumes limited incrementality, full parallelism: not cognitively plausible;
- left-corner parsing models achieves a higher degree of incrementality;
- to model garden paths, we can assume serial parsing with backtracking.